

Product Range

ALUCOBOND®	Thickness: 3mm / 4mm / 6mm					
	Width	1000mm	1250mm	1500mm	1575mm	1750mm
	Length	2000-6800mm	2000-11000mm	2000-11000mm	2000-11000mm	2000-11000mm
Solid Colours		■	■	■	■	■
Metallic Colours		■	■	■	■	■
Special Effect Colours		■	■	■	■	■
Spectra Colours		■	■	■	■	-
NaturAL		-	■	■	-	-
Wood Design		-	■	■	-	-
Anodized Look		■	■	■	■	-
Anodized*		■	■	■	-	-
Mill Finish		■	■	■	-	-

Not all finishes available ex stock.



ALUCOBOND® plus	Thickness: 4mm					
	Width	1000mm	1250mm	1500mm	1575mm	1750mm
	Length	2000-6800mm	2000-11000mm	2000-11000mm	2000-11000mm	2000-11000mm
Solid Colours		■	■	■	■	■
Metallic Colours		■	■	■	■	■
Special Effect Colours		■	■	■	■	■
Spectra Colours		■	■	■	■	-
NaturAL		-	■	■	-	-
Wood Design		-	■	■	-	-
Anodized Look		■	■	■	■	-
Anodized*		■	■	■	-	-
Mill Finish		■	■	■	-	-



ALUCOBOND® A2	Thickness: 3mm / 4mm					
	Width	1000mm	1250mm	1500mm	1575mm	1650mm
	Length	2000-9600mm	2000-9600mm	2000-9600mm	2000-9600mm	2000-9600mm
Solid Colours		-	■	■	-	■
Metallic Colours		-	■	■	-	■
Special Effect Colours		-	■	■	-	■
Spectra Colours		-	■	■	-	-
NaturAL		-	-	-	-	-
Wood Design		-	■	■	-	-
Anodized Look		-	■	■	-	-
Anodized*		-	-	-	-	-
Mill Finish		-	■	■	-	-

Other specifications upon request.



SPECIALITIES						
ALUCORE® aluminium honeycomb composite panel						
	Thickness: 6mm** / 10mm / 15mm / 16mm / 25mm					
	Width	1000mm	1250mm	1500mm	1575mm	1750mm
	Length	2000-9600mm (13000mm)	2000-9600mm (13000mm)	2000-9600mm (13000mm)	2000-9600mm (13000mm)	2000-9600mm (13000mm)
Solid Colours		-	■	■	-	-
Metallic Colours		-	■	■	-	-
Anodized Look		-	■	■	-	-
Mill Finish		-	■	■	-	-

* On request



ALUCOBOND® photovoltaic is an integration of photovoltaic elements into an ALUCOBOND® façade. We supply the complete system.

Modules	Dimensions	Colours	Weight	Output	Mounting System
CIGS	1196mm x 636mm	Black	14.5kg with frame	75 Wp +/-0%	Adapted to standard ALUCOBOND® façade systems
Monocrystalline module	1654mm x 829mm	Anthracite	19.0kg with frame	75 Wp +/-0%	Adapted to standard ALUCOBOND® façade systems

* Anodized according to DIN 17611. All anodized ALUCOBOND® composite panels have contact lines (about 25mm width) on their short sides. For panel lengths of more than 4000 mm, the composite panels have contact lines (about 2 – 3mm width) on their long sides. Please take this into consideration when dimensioning the panels.

DISTRIBUTED BY



ALUCOBOND ARCHITECTURAL
A Division of Halifax Vogel Group Pty Limited
VICTORIA: (03) 9394 3130
NEW SOUTH WALES: (02) 8525 6900
QUEENSLAND: (07) 3718 2360
WESTERN AUSTRALIA: (08) 9494 0100
SOUTH AUSTRALIA: (08) 8348 6800
info@alucobond.com.au
www.alucobond.com.au

