

# Two Way Tape

## DOUBLE SIDED TAPE FOR RAPID ATTACHMENT

- Extra strong, high tensile strength and elasticity.
- Oil, petrol, diesel, chemical and weather resistant.
- Clean and simple to use.
- Permanent adhesion on clean surfaces.
- Repositionable.

## General information

TWO WAY TAPE consists of a 0.8 mm black, cross-linked, closed cell, polyethylene foam, coated on both sides with an acrylic adhesive. TWO WAY TAPE offers very high adhesive and cohesive properties, with the possibility of repositioning. TWO WAY TAPE has a high holding power and an

excellent resistance to weathering and oil. TWO WAY TAPE is available in five different dimensions to make the job easier.

## Technical information and packaging

Foam: black, cross-linked, closed-cell polyethylene.  
 Adhesive: acrylic resin, reacts to pressure.  
 Backing: one side silicone coated green polyethylene film.  
 Density: 100 kg/m<sup>3</sup>  
 Adhesion to steel: g/20 mm (7 days/20°C).  
 Shear strength: 7.5 kg/cm<sup>2</sup>.  
 Features: high holding power; excellent resistance to weathering and oil.  
 End use temperature range after 7 days: -40°C

to +100°C.  
 Min. application temperature: +10°C.  
 Thickness: 0.9mm.  
 First test foundations based on PE, PP, silicones and bitumen for adhesion (see each tape).  
 Shelf life: 24 months, keep dry, cool and frost-proof.  
 Safety measures: consult the Safety Data Sheet.

## Applications and use

- mounting of automotive side mouldings and emblems
- mounting of name-plates and letters
- mounting of interior and exterior coverings
- mounting of air-spoilers
- mounting of electronic components
- ideal for use with high fluctuations of temperature

## Product references

Article nr	Name	Content	Section
550068000	Two Way Tape	Roll 6mm x 10m	tapes
550128000	Two Way Tape	Roll 12mm x 10m	tapes
550158000	Two Way Tape	Roll 15mm x 10m	tapes
550198000	Two Way Tape	Roll 19mm x 10m	tapes
550258000	Two Way Tape	Roll 25mm x 10m	tapes

