

# Product Overview



# Product Overview Descripción del producto Aperçu des produits



Produktgruppe product range	Kollektion collection				dekodur LAMINATE TECHNOLOGY	Abmessung dimension	Stärke thickness	Qualität quality	Seite page
<b>dekovario</b>		Strukturen	structures	Estructura colección	—				6–11, 16–17 24–25, 52–53
<b>dekopuls</b>	dekolor	Unifarben	solid colors	Superficies unicolores	✓	2440 x 1220 mm	0,8 mm	ST, NF	12–14
HPL / DIN EN 438	dekocore	durchgefärbter Kern	with core dyed throughout	LAP con núcleo coloreado	—	2440 x 1220 mm	0,8–1,2 mm	ST	15
	dekopin	magnethaftend	magnetic HPL	magnética	✓	2440 x 1220 mm	0,8–1,2 mm	ST	18–19
	dekonova	Fantasie- und Holzdekore	fantasy and wooden designs	Decoraciones fantasía	✓	2440 x 1220 mm	0,8–1,2 mm	ST, NF	20–23
	<b>Graviermaterial</b>	Graviermaterial	engraving material	Material grabado	—	605 x 1220 mm 805 x 1220 mm	1,0–3,0 mm	ST	26–27
<b>dekopix</b>		Digitaldrucke in HPL	digital print in HPL	Digital en HPL	✓	2440 x 1220 mm	0,8 mm	ST	28–29
<b>dekorial</b>	starline	Aluminium	aluminum	Aluminio	✓	2440 x 1220 mm* (3050 x 1320 mm)*	0,8–0,9 mm	ST, NF	30–35
- Echtmittel-Oberflächen - Genuine metal surfaces - Superficies de metal genuino	dekostyle metal	Aluminium gestanz	aluminum punched	Aluminio perforado	✓	2440 x 1220 mm	0,8 mm	ST	36–39
	dekostyle wood	Holzoberflächen gestanz	wooden surfaces punched	Superficies de madera sellada	✓	2440 x 1220 mm	0,8 mm	ST	40–41
	inox	Edelstahl	stainless steel	Acero inoxidable	✓	2440 x 1220 mm* (2440 x 1000 mm)*	0,8 mm	ST	42–45
	stratos	Aluminium gebürstet	aluminum grinding patterns	Aluminio cepillado	✓	2440 x 1220 mm	0,8 mm	ST	46–49
	antique	Kupfer	copper	Cobre	✓	2440 x 1220 mm	1,2 mm	ST	50–51
	rustikal	Zinn	tin	Estaño	✓	2440 x 1220 mm	1,2 mm	ST	54–57
<b>dekolux</b>	toplux	Transluzentes HPL/Gewebe	translucent HPL/Fabric	translúcido HPL/Tejido	—	2440 x 1220 mm	1,5 mm	ST	58–59
	starlux	Transluzentes HPL/Alu gestanz	translucent HPL/Alu punched	translúcido HPL/Alu punzonado	—	2440 x 1220 mm	1,5 mm	ST	60–63
	fossil	Transluzentes HPL/Bernstein	translucent HPL/Amber	translúcido HPL/Ámbar	—	2440 x 1220 mm	1,8 mm	ST	64–65
<b>dekoart</b>	art concept	Künstlermotive in HPL	artists' motifs in HPL	Motivos artísticos en HPL	✓	2440 x 1220 mm	1,0 mm	ST	66–71
	unique art	Künstlermotive in Kupfer	artists' motifs in cooper	Motivos artísticos en cobre	✓	2440 x 1220 mm	1,2 mm	ST	72–77
	royal art	Künstlermotive mit Gold	artists' motifs with gold	Motivos artísticos con oro	✓	2440 x 1220 mm	1,0 mm	ST	78–81
<b>dekobond</b>		HPL in Glas	HPL in glass	HPL en Cristal	—	2440 x 1220 mm	4,0–12,0 mm	ST	82–83
<b>deko wood</b>	veneer	Echtholz-Oberflächen	real wood surfaces	Real de superficie	✓	2440 x 1220 mm	0,8 mm	ST	84–87
	bark cloth	Rindentuch	bark cloth	Superficies de madera auténtica	✓	2440 x 1220 mm	0,8 mm	ST	88–91
<b>dekospan</b>		Verbundelemente	compound elements	Eöements de unión	—	2440 x 1220 mm* (3050 x 1320 mm)*	13, 16, 19 mm		92
		Direktbeschichtung (Metall)	directly faced chipboard (Metal)	Recubrimientos directos (Metal)	—	3650 x 1250 mm			92
		Postforming-Elemente	postforming elements	Elementos de acabado	—				92
<b>dekofoil</b>		Ummantelungsfolie	wrapping foil	Películas de revestimiento	—	Rolle* / 1300 mm	0,2–0,4 mm	ST, NF	93
		Kantenmaterial	edgebanding material	Material para bordes	—				93
		Endloslaminat	endless laminate	Laminado continuo	—				93
<b>deko film</b>		Imprägnierte Papiere	impregnated paper	Papeles impregnados	—	auf Anfrage	auf Anfrage	auf Anfrage	94

ST = Standardqualität  
NF = Postformingqualität

ST = standard quality  
NF = post forming quality

ST = Calidad estándar  
NF = Calidad postmoldeado

ST = qualité standard  
NF = qualité postforming

\* angegebene Plattengröße/Rollengröße auf Anfrage erhältlich. Spezialstärken bis 4,0 mm auf Anfrage erhältlich.

\* The sheet/roll sizes quoted are obtainable upon request. Special strengths of up to 4,0 mm are obtainable upon request.

\* Las planchas están disponibles a petición en el tamaño indicado. Grosos especiales hasta 4,0 mm están disponibles a petición.

\* Dimensions de panneau/rouleau indiquées disponibles sur demande. Épaisseurs spéciales jusqu'à 4,0 mm disponibles sur demande.