



Lloyd's
Register

Lloyd's Register EMEA

71 Fenchurch Street, London, EC3M 4BS

Telephone 020 7423 2416 Fax 020 7423 2053

Email med@lr.org

Page	2 of 2
Document number	SAS F140323
Issue number	1

DESIGN APPRAISAL DOCUMENT

Date 29 November 2014	Quote this reference on all future communications MTES/TA/SFS/JE/WP19373453
--------------------------	--

ATTACHMENT TO CERTIFICATE OF TYPE APPROVAL No. SAS F140323

This Design Appraisal Document forms part of the Certificate.

APPROVAL DOCUMENTATION

TUV Nord (Brandversuchshaus Hamburg), Morkenstrabe 36, D-22767 Hamburg, Germany, Fire Test Reports No. SN02/2480.2 and TN02/2508.2 both dated 20th May 2003.

CONDITIONS OF CERTIFICATION

1. When applied to a non-combustible substrate.
2. Decorative high pressure laminate comprising: resin impregnated paper (0.8mm thick, weight 1350g/m²) bonded to substrate with 'DORUS FU 406/1' adhesive applied at rate 120g/m².
3. Composition of individual components, including any fire retardants, to be maintained in production in accordance with originally tested composition formula and applied in accordance with manufacturer's instructions.
4. Production items are to be manufactured in accordance with a quality control system which shall be maintained to ensure that items are of the same standard as the approved prototype.

PLACE OF PRODUCTION

Dekodur GmbH & Co. KG
Langenthaler Strabe 4
69434 Hirschhorn / Neckar
Germany



J. M. Evans
Senior Surveyor
Statutory Fire & Safety
Marine Technology and Engineering Services
Lloyd's Register EMEA

Supplementary Type Approval Terms and Conditions

This certificate and Design Appraisal Document relates to type approval, it certifies that the prototype(s) of the product(s) referred to herein has/have been found to meet the applicable design criteria for the use specified herein, it does not mean or imply approval for any other use, nor approval of any products designed or manufactured otherwise than in strict conformity with the said prototype(s).